

| | |
|------------------|------------------------------------|
| Model | UL-1 |
| Lamp: | MR16 Halogen or LED |
| Maximum Wattage: | 35 watt, 8 watt LED |
| Input Voltage: | 12V (remote transformer required) |
| Material: | Machined Aluminum |
| Hardware: | Stainless Steel |
| Finishes: | Seven Polyester Powder Coat |
| Lens: | Tempered Clear Glass, Flush lens |
| Cap Accessories: | Holds Three accessories (optional) |
| Mounting: | 1/2" NPS (order mount separately) |
| Socket: | GY-6.35 Bi Pin Porcelain |
| IP Rating: | 66 |
| Certification: | Wet location |
| Wiring: | 10" 18 ga Teflon Coated |
| Weight: | .8 lbs. |
| Warranty: | 10 Years |
| Dimensions: | 2 3/8" dia. x 3 3/4" long |



Shown in Bronze Powder Coat Finish (BZ)



SORAA DAUER BRILLIANCE



METALS:

6061-T6 Aluminum



Mounting Stake Options:



ORDERING LOGIC:

| | | |
|---------|---|--|
| Model: | UL - 1 | |
| Metal: | A - Aluminum | |
| Finish: | BK - Black BZ - Bronze WT - White BG - Beige | BKT - Black Texture BZT - Bronze Texture SL - Silver AC - Aged Copper |

ORDERING EXAMPLE: UL - 1 - A - BK

FLUSH LENS FEATURE:



To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model UL-1. Caps drain water even when aimed straight up.

ANODIZING PROTECTION:



To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.