

Model	UL-7
Lamp:	MR16 Halogen or LED
Maximum Wattage:	35 watt, 8 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Tempered Clear Glass, Flush lens
Cap Accessories:	Holds Three accessories (optional)
Mounting:	1/2" NPS (order mount separately)
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location
Wiring:	10" 18 ga Teflon Coated
Weight:	.10 lbs.
Warranty:	10 Years
Dimensions:	2 3/8" dia. x 7 1/2" long



Shown in Bronze Powder Coat Finish (BZ)







SORAA

DAUER

BRILLIANCE







METALS:

6061-T6 Aluminum



Mounting Stake Options:

MT-1 MT-6 MT-8

FLUSH LENS FEATURE:

To reduce the amount of mineral deposits that build up on the fixture lens, our 'Flush Lens' feature is standard on our Model UL-7. Caps drain water even when aimed straight up.



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

- 1. Machine 6061-T6 copper-free aluminum.
- 2. Anodized pre-treatment applied.
- 3. Polyester powder coat finish applied.

ORDERING LOGIC:

UL-7 Model:

Metal: A - Aluminum

Finish: BK - Black BKT - Black Texture BZ - Bronze BZT - Bronze Texture

WT - White SL - Silver

BG - Beige AC - Aged Copper



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment. The socket is replaceable because it is not glued in.

ORDERING EXAMPLE: UL - 7 - A - BK