

Model	RL-4
Lamp:	MR11 Halogen (order separately)
Maximum Wattage:	20 watt, 3 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Lens:	Frosted Acrylic Liner/Clear Glass Lens
Mounting:	Brass 1 inch loop
Socket:	GY 6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location
Wiring:	12" 18 ga Shrink Tube Covered, black
Weight:	.5 lbs.
Warranty:	10 Years
Dimensions:	1 3/4" dia. x 9" overall



Shown in Bronze Texture Powder Coat Finish (BZT)



DAUER



ELI



BRILLIANCE



METALS:

6061-T6 Aluminum



Optional Frosted Lens at Bottom



Frosted Acrylic Liner is Standard



STAINLESS STEEL CABLE:

We can provide 1/16" stainless steel cable with hardware if you like. Select from various lengths from 5'-30', in five foot increments. Contact factory for more information.

ORDERING LOGIC:

Model:	RL - 4		
Metal:	A - Aluminum		
Bottom Lens:	0 - None 1 - Frosted lens glued in		
SS Cable:	0 - None	15 - 15 ft	30 - 30 ft
	5 - 5 ft	20 - 20 ft	
	10 - 10 ft	25 - 25 ft	
1/2 Wire:	0 - None	15 - 15 ft	30 - 30 ft
	5 - 5 ft	20 - 20 ft	
	10 - 10 ft	25 - 25 ft	
Finish:	BK - Black	BKT - Black Texture	
	BZ - Bronze	BZT - Bronze Texture	
	WT - White	SL - Silver	
	BG - Beige	CA - Clear Anodized	



ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Black anodized pre-treatment applied.
3. Polyester powder coat finish applied.



SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.

ORDERING EXAMPLE: RL - 4 - A - 1 - 0 - 0 - BK