Model	FA-20
Lamp:	MR16 Halogen, LED (order separately)
Maximum Wattage:	75 watt, 9 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Machined Aluminum
Hardware:	Stainless Steel
Finishes:	Seven Polyester Powder Coat
Knuckle:	Tapered & Positive Locking
Lens:	Tempered Clear Glass, 30° angle
Cap Accessories:	Holds Three accessories (optional)
Mounting:	1/2” NPS (order mount separately)
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location
Wiring:	2ft. 18/2 LV wire leads
Weight:	2.1 lbs.
Warranty:	10 Years
Dimensions:	3” dia. x 7” overall

Shown in Bronze Powder Coat Finish (BZ)

SORAA ELI BRILLIANCE

Made in USA

METALS:

6061-T6 Aluminum

Mounting Stake Options:

MT-1 MT-2 MT-6 MT-7 MT-8

ANODIZING PROTECTION:

To increase the corrosion resistance in our products, we use a three-step process:

1. Machine 6061-T6 copper-free aluminum.
2. Anodized pre-treatment applied.
3. Polyester powder coat finish applied.

ORDERING LOGIC:

Model:	FA - 20	
Metal:	A - Aluminum	
Finish:	BK - Black	BKT - Black Texture
	BZ - Bronze	BZT - Bronze Texture
	WT - White	SL - Silver
	BG - Beige	AC - Aged Copper

ORDERING EXAMPLE: FA - 20 - A - BK

Xseal™

SEALED WIRE PASS-THRU SYSTEM:

Our molded, high-temperature silicone wire pass-thru system is installed into every product to prevent water intrusion. Water will not leak into the lamp compartment when used for downlighting in trees. The socket is replaceable because it is not glued in.