

Model	IN-10L
Lamp:	LED Module: 2W - 9W Adjustable
Wattage:	12W Startup draw
Input Voltage:	12VAC/DC (remote magnetic transformer required)
Kelvin:	2700K, 3000K, 4000K. CRI = 85
Material:	Cast Aluminum frame & grate
Hardware:	Stainless Steel
Finishes:	Natural, Dark Bronze or Powder Coat
Aiming:	15 Degrees
Lens:	Tempered Clear Glass, Flush lens
Accessories:	Holds two accessories (optional)
Mounting:	In Ground/Concrete Pour
Socket:	GY 6.35 Bi-pin porcelain
Certification:	Wet location, IP Rating = 67
Wiring:	6' 16/2 low voltage cable
Weight:	11.4 lbs.
Warranty:	25 Years
Dimensions:	6 5/8" diameter x 11 1/4" tall



Shown in Natural Bronze Finish (NT)



2W/4W/6W/9W



METALS:

Cast Aluminum



SELECT-A-FIT:

Exclusively from Excelsior Lighting, our Xset feature allows you to set your own fixture location within our Models IN4 and IN5 well lights. This feature helps provide the proper fixture location for your lamp beam spread. Spot lamps can be located deeper into the fixture while wide floods can be located closer to the fixture grate. Our simple design offers three grooved locations on the outside of the fixture cap, one inch apart. Simply decide which setting is best for your application and snap the fixture into place!

ORDERING LOGIC:

Model:	IN - 10L	
Metal:	A - Aluminum	
Fixture Regress:	1 - 1 3/4" 2 - 3" (standard)	
Finish:	BK - Black BZ - Bronze WT - White BG - Beige NT - Natural	BKT - Black Texture BZT - Bronze Texture SL - Silver DB - Dark Bronze AC - Aged Copper

ORDERING EXAMPLE: IN - 10L - A - 1 - NT - 52*

*See Module sheet to select module type to be installed

9W MULTI-LEVEL - 2W, 4W, 6W, 9W (165-860 Lumens)



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four light levels, 2700K, 3000K, or 4000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangeable lenses: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- L70=60,000 hours
- 3 Year warranty
- FCC Compliant
- RoHS Compliant
- Pb Free
- Field Replaceable



#	Specifications	Lumens
50	2W - 9W, 2700K, 15°	165-720
51	2W - 9W, 2700K, 30°	165-720
52	2W - 9W, 2700K, 45°	165-720
60	2W - 9W, 2700K, 60°	165-720
53	2W - 9W, 3000K, 15°	190-800
54	2W - 9W, 3000K, 30°	190-800
55	2W - 9W, 3000K, 45°	190-800
61	2W - 9W, 3000K, 60°	190-800
62	2W - 9W, 4000K, 15°	210-860
63	2W - 9W, 4000K, 30°	210-860
64	2W - 9W, 4000K, 45°	210-860
65	2W - 9W, 4000K, 60°	210-860

Wattage	2700k	3000K	4000K
2W	165 lms	190 lms	210 lms
4W	345 lms.	360 lms.	385 lms
6W	515 lms.	530 lms.	590 lms
9W	720 lms.	800 lms.	860 lms

LENSES INCLUDED

15°



45°



30°



60°

