

Simply Better by Design™

Model	PL-16
Lamp:	T4 Halogen or LED
Maximum Wattage:	35 watt, 3 watt LED
Input Voltage:	12V (remote transformer required)
Material:	Aluminum or brass - 1 1/4" square
Hardware:	Stainless Steel
Finishes:	Seven Powder Coat, Two Metals
Lens:	Frosted Acrylic
Mounting:	1/2" NPS (order mount separately)
Height:	9", 12" or 18"
Socket:	GY-6.35 Bi Pin Porcelain
IP Rating:	66
Certification:	Wet location landscape, UL1838
Wiring:	6 ft. 16/2 low voltage cable
Weight:	Brass: 1.8 lbs., Aluminum: 5.1 lbs.
Warranty:	Brass: 25 Years Aluminum: 10 Years
Dimensions:	1 1/4" Square tube



Shown in Clear Anodized Finish (CA)









(wildlife)

DAUER

BRILLIANCE

JQ









Aluminum:

Brass:



ORDERING LOGIC:

Model: PL - 16

Metal: A - Aluminum

B - Brass

Height: 9 - 9"

12 - 12" 18 - 18"

Finish: BK - Black **BKT - Black Texture**

BZ - Bronze BZT - Bronze Texture

WT - White SL - Silver

CA - Clear Anodized BG - Beige NT - Natural DB - Dark Bronze

ORDERING EXAMPLE: PL - 16 - B - 18- DB

MODULAR DESIGN:

The PL-16 path light is available in aluminum or brass square tubing. The components that house and seal the lamp are machined from copper-free aluminum, then anodized to prevent corrosion from all types of elements. Stainless steel hardware and silicone o-ring seals are standard features. To relamp this luminaire, simply remove one screw and slide out the lamp housing.

Mounting Stake Options:

MT-45 MT-6 MT-8

